



SPECIFICATIONS

- Submersible up to 15 ft / 5 m
- Manufactured from 14 gauge Type 316 Marine Grade Stainless Steel
- Seams continuously welded and dressed
- Single piece Neoprene gasket
- Minimum flange width to maximize internal capacity
- Mounting brackets on enclosure rear for direct wall mounting
- Grounding stud on body
- Mounting studs for optional internal mount plates
- #3 polish finish

ACCESSORIES

- Internal Mount/Back Plates
- External ground mounting stand
- Custom entry holes
- IP68 Stainless Steel cable glands / chord grips
- EMI / RFI Shielding Protection Available
- Hinged Lid
- Welded in place Bosses
- Variety of finishes

INDUSTRY STANDARDS

Meets NEMA Type 6P requirements

NEMA 4,4X,6P and IP68

APPLICATION

SLAYSON Submersible **Compact Series** offers NEMA 6P / IP68 protection against water and dust ingress at depths up to 15ft / 5m. Submersible Standard Enclosures are manufactured as standard from 14g Marine Grade 316 Stainless Steel, ensuring protection in harsh and corrosive environments.

MODIFICATION AND CUSTOMIZATION

SLAYSON excels at modifying and customizing all our products to meet your exact specifications. Contact our experienced Engineers about your project specific solution.

PART NUMBER	A	B	C	D Mount	E Mount	BACK PLATE PART NUMBER	Height:	Width:	Gauge	Weight (lbs)
	Height: in (mm)	Width: in (mm)	Depth: in (mm)	Height: in (mm)	Width: in (mm)		in (mm)	in (mm)		
ASMI202008	20 (508)	20 (508)	08 (203.2)	16 (406.4)	22 (558.8)	ASPI1616	16 (406.4)	16 (406.4)	14	25
ASMI202006	20 (508)	20 (508)	06 (152.4)	16 (406.4)	22 (558.8)	ASPI1616	16 (406.4)	16 (406.4)	14	24
ASMI181808	18 (457.2)	18 (457.2)	08 (203.2)	14 (355.6)	20 (508)	ASPI1414	14 (355.6)	14 (355.6)	14	24
ASMI181806	18 (457.2)	18 (457.2)	06 (152.4)	14 (355.6)	20 (508)	ASPI1414	14 (355.6)	14 (355.6)	14	22
ASMI161608	16 (406.4)	16 (406.4)	08 (203.2)	12 (304.8)	18 (457.2)	ASPI1212	12 (304.8)	12 (304.8)	14	22
ASMI161606	16 (406.4)	16 (406.4)	06 (152.4)	12 (304.8)	18 (457.2)	ASPI1212	12 (304.8)	12 (304.8)	14	20
ASMI141408	14 (355.6)	14 (355.6)	08 (203.2)	10 (254)	16 (406.4)	ASPI1010	10 (254)	10 (254)	14	20
ASMI141406	14 (355.6)	14 (355.6)	06 (152.4)	10 (254)	16 (406.4)	ASPI1010	10 (254)	10 (254)	14	18
ASMI121208	12 (304.8)	12 (304.8)	08 (203.2)	08 (203.2)	14 (355.6)	ASPI0808	08 (203.2)	08 (203.2)	14	18
ASMI121206	12 (304.8)	12 (304.8)	06 (152.4)	08 (203.2)	14 (355.6)	ASPI0808	08 (203.2)	08 (203.2)	14	16
ASMI101008	10 (254)	10 (254)	08 (203.2)	06 (152.4)	12 (304.8)	ASPI0606	06 (152.4)	06 (152.4)	14	16
ASMI101006	10 (254)	10 (254)	06 (152.4)	06 (152.4)	12 (304.8)	ASPI0606	06 (152.4)	06 (152.4)	14	14