



**SPECIFICATIONS**

- Submersible up to 15 ft / 5 m
- Manufactured from 14 gauge Type 316 Marine Grade Stainless Steel
- Seams continuously welded and dressed
- Single piece Neoprene gasket
- Minimum flange width to maximize internal capacity
- Mounting brackets on enclosure rear for direct wall mounting
- Grounding stud on body
- Mounting studs for optional internal mount plates
- #3 polish finish

**ACCESSORIES**

- Internal Mount/Back Plates
- External ground mounting stand
- Custom entry holes
- IP68 Stainless Steel cable glands / chord grips
- EMI / RFI Shielding Protection Available
- Hinged Lid
- Welded in place Bosses
- Variety of finishes

**INDUSTRY STANDARDS**

Meets NEMA Type 6P requirements  
NEMA 4,4X,6P and IP68

**APPLICATION**

SLAYSON Submersible **Watershed Series** offers NEMA 6P / IP68 protection against water and dust ingress at depths up to 15ft / 5m. Submersible Standard Enclosures are manufactured as standard from 14g Marine Grade 316 Stainless Steel, ensuring protection in harsh and corrosive environments.

**MODIFICATION AND CUSTOMIZATION**

SLAYSON excels at modifying and customizing all our products to meet your exact specifications. Contact our experienced Engineers about your project specific solution.

PART NUMBER	A	B	C	D Mount	E Mount	BACK PLATE PART NUMBER	Height:	Width:	Gauge	Weight (lbs)
	Height: in (mm)	Width: in (mm)	Depth: in (mm)	Height: in (mm)	Width: in (mm)		in (mm)	in (mm)		
WSMI363624	36 (914.4)	36 (914.4)	24 (609.6)	38 (956.2)	34 (863.6)	ASPI3434	34 (863.6)	34 (863.6)	14	53
WSMI363612	36 (914.4)	36 (914.4)	12 (304.8)	38 (956.2)	34 (863.6)	ASPI3434	34 (863.6)	34 (863.6)	14	45
WSMI343424	34 (863.6)	34 (863.6)	24 (609.6)	36 (914.4)	32 (812.8)	ASPI3232	32 (812.8)	32 (812.8)	14	51
WSMI343412	34 (863.6)	34 (863.6)	12 (304.8)	36 (914.4)	32 (812.8)	ASPI3232	32 (812.8)	32 (812.8)	14	43
WSMI303018	30 (762)	30 (762)	18 (457.2)	32 (812.8)	28 (711.2)	ASPI2828	28 (711.2)	28 (711.2)	14	43
WSMI302618	30 (762)	26 (660.4)	18 (457.2)	32 (812.8)	28 (711.2)	ASPI2824	28 (711.2)	24 (609.6)	14	41
WSMI282816	28 (711.2)	28 (711.2)	16 (406.4)	30 (762)	26 (660.4)	ASPI2626	26 (660.4)	26 (660.4)	14	40
WSMI262616	26 (660.4)	26 (660.4)	16 (406.4)	28 (711.2)	24 (609.6)	ASPI2424	24 (609.6)	24 (609.6)	14	37
WSMI262614	26 (660.4)	26 (660.4)	14 (355.6)	28 (711.2)	24 (609.6)	ASPI2424	24 (609.6)	24 (609.6)	14	36
WSMI262214	26 (660.4)	22 (558.8)	14 (355.6)	28 (711.2)	20 (508)	ASPI2420	24 (609.6)	20 (508)	14	34
WSMI242412	24 (609.6)	24 (609.6)	12 (304.8)	26 (660.4)	22 (558.8)	ASPI2222	22 (558.8)	22 (558.8)	14	33
WSMI221212	22 (558.8)	12 (304.8)	12 (304.8)	24 (609.6)	14 (355.6)	ASPI2010	20 (508)	10 (254)	14	25