DEEP COMPACT SUBMERSIBLE ENCLOSURE

HydroLine™



SPECIFICATIONS

- NEMA 6P / IP68 / IK10
- UL / CSA Tested to 6 ft / 2 mtr (UL508A)
- Submersible up to 15 ft / 5 mtr (IEC 60529)
- Corrosion Resistant Salt Spray Test (ASTM B117)
- Stainless Steel Type 316 Fasteners & Hardware
- Trough Collar Sealing Flange
- Seams continuously welded & ground smooth
- Single piece Neoprene Gasket
- Internal Strengthening Rails for flexible Mounting Options
- High Impact & Crush Resistance (IK10)

MATERIAL	CODE
Stainless Steel Type 316, 14 gauge | 2.00mm*	S

FINISH	
#4 Surface Finish*	M

*Alternative finish & material options available

INDUSTRY STANDARDS

UL 508A Listed, Type 4X, 6, 6P, File No. E548541 CUL
Listed per CSA C22.2 No. 14, Type 4, 12 File No. E548541

NEMA Type 6P, IP67/68 IEC 60529
IK10 Impact Resistant

APPLICATION

The HydroLine™ DEEP COMPACT SUBMERSIBLE Enclosure is the industry standard for power & utility, infrastructure and renewal energy companies requiring ultimate protection against extreme environmental conditions. Manufactured from corrosion resistant Stainless Steel Type 316 and a single piece Neoprene Gasket to provide watertight protection of vital electrical equipment. SLAYSON's HydroLine™ STANDARD SUBMERSIBLE range of enclosures and accessories delivers a reliable enclosure system to meet all industry environmental challenges.

MODIFICATION & CUSTOMIZATION

SLAYSON® excels at modifying and customizing all our products to meet your exact specifications. Whether you require custom engraving and decals, connector through-hole cutouts, welded in-place accessories, or a non-standard size, contact our experienced engineers to discuss your project-specific solution.

ACCESSORIES


Internal Mount Plate	B
Hinged Lid / Door	H
Optical Window Lid / Door	O
Security Lock Tab	P
Nameplate	N
Captive Lid Fasteners	C
Internal Swing Out Panel	S
Shock & Vibration Mount Kit	V
360° EMC / EMP Shielding Gasket	E
External Grounding Stud	G
Lifting Eye Hooks	L
Raised Floor Mounting Plinths	R
Heavy Duty Gusset Mount Tabs	T
Lid / Door Stay	D
Access Door (IP66)	A
Pull Handle	U
Document Pocket	M
Welded In-Place Hubs	*
Welded In-Place Studs	*
Cable Glands / Cord Grips	*
NPT Cable Glands	*


*Customer Modification Code is required when the Accessory component selected requires any of the following: enclosure cutouts, through holes or penetrations, customer involved design for accessory placement. This code is added in front of the part number by SLAYSON® to provide a unique identifier for customer specific engineering data.

PART NUMBER BUILDER

Customer Mod Code*			Material	Imperial	A Height (in)		B Width (in)		C Depth (in)		Accessory Codes		
		–	B	S	M	I	2	2	2	2	1	6			
			Enclosure Seres		Submersion Depth		For Non-Standard sizes or to add Optional Accessories use the Part Number Builder to configure the part number.								

*Generated by SLAYSON Engineering for customer specific modifications





DEEP COMPACT SUBMERSIBLE ENCLOSURE

PART NUMBER	A		B		C		D		E		INTERNAL MOUNT PLATE				Gauge
	Height		Width		Depth		Mount Height		Mount Width		Height		Width		
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	
BSMI222216	22	558.8	22	558.8	16	406.4	18	457.2	24	609.6	18	457.2	18	457.2	14
BSMI222212	22	558.8	22	558.8	12	304.8	18	457.2	24	609.6	18	457.2	18	457.2	14
BSMI222210	22	558.8	22	558.8	10	254.0	18	457.2	24	609.6	18	457.2	18	457.2	14
BSMI222208	22	558.8	22	558.8	08	203.2	18	457.2	24	609.6	18	457.2	18	457.2	14
BSMI221612	22	558.8	16	406.4	12	304.8	18	457.2	18	457.2	18	457.2	12	304.8	14
BSMI221610	22	558.8	16	406.4	10	254.0	18	457.2	18	457.2	18	457.2	12	304.8	14
BSMI221608	22	558.8	16	406.4	08	203.2	18	457.2	18	457.2	18	457.2	12	304.8	14
BSMI221606	22	558.8	16	406.4	06	152.4	18	457.2	18	457.2	18	457.2	12	304.8	14
BSMI221210	22	558.8	12	304.8	10	254.0	18	457.2	14	355.6	18	457.2	08	203.2	14
BSMI221208	22	558.8	12	304.8	08	203.2	18	457.2	14	355.6	18	457.2	08	203.2	14
BSMI221206	22	558.8	12	304.8	06	152.4	18	457.2	14	355.6	18	457.2	08	203.2	14
BSMI202016	20	508.0	20	508.0	16	406.4	16	406.4	22	558.8	16	406.4	16	406.4	14
BSMI202012	20	508.0	20	508.0	12	304.8	16	406.4	22	558.8	16	406.4	16	406.4	14
BSMI202008	20	508.0	20	508.0	08	203.2	16	406.4	22	558.8	16	406.4	16	406.4	14
BSMI202006	20	508.0	20	508.0	06	152.4	16	406.4	22	558.8	16	406.4	16	406.4	14
BSMI201412	20	508.0	14	355.6	12	304.8	16	406.4	16	406.4	16	406.4	10	254.0	14
BSMI201410	20	508.0	14	355.6	10	254.0	16	406.4	16	406.4	16	406.4	10	254.0	14
BSMI201408	20	508.0	14	355.6	08	203.2	16	406.4	16	406.4	16	406.4	10	254.0	14
BSMI201406	20	508.0	14	355.6	06	152.4	16	406.4	16	406.4	16	406.4	10	254.0	14
BSMI201210	20	508.0	12	304.8	10	254.0	16	406.4	14	355.6	16	406.4	08	203.2	14
BSMI201208	20	508.0	12	304.8	08	203.2	16	406.4	14	355.6	16	406.4	08	203.2	14
BSMI201206	20	508.0	12	304.8	06	152.4	16	406.4	14	355.6	16	406.4	08	203.2	14
BSMI181814	18	457.2	18	457.2	14	355.6	14	355.6	20	508.0	14	355.6	14	355.6	14
BSMI181812	18	457.2	18	457.2	12	304.8	14	355.6	20	508.0	14	355.6	14	355.6	14
BSMI181808	18	457.2	18	457.2	08	203.2	14	355.6	20	508.0	14	355.6	14	355.6	14
BSMI181806	18	457.2	18	457.2	06	152.4	14	355.6	20	508.0	14	355.6	14	355.6	14
BSMI181412	18	457.2	14	355.6	12	304.8	14	355.6	16	406.4	14	355.6	10	254.0	14
BSMI181410	18	457.2	14	355.6	10	254.0	14	355.6	16	406.4	14	355.6	10	254.0	14
BSMI181408	18	457.2	14	355.6	08	203.2	14	355.6	16	406.4	14	355.6	10	254.0	14
BSMI181406	18	457.2	14	355.6	06	152.4	14	355.6	16	406.4	14	355.6	10	254.0	14
BSMI181210	18	457.2	12	304.8	10	254.0	14	355.6	14	355.6	14	355.6	08	203.2	14
BSMI181208	18	457.2	12	304.8	08	203.2	14	355.6	14	355.6	14	355.6	08	203.2	14
BSMI181206	18	457.2	12	304.8	06	152.4	14	355.6	14	355.6	14	355.6	08	203.2	14
BSMI161612	16	406.4	16	406.4	12	304.8	12	304.8	18	457.2	12	304.8	12	304.8	14
BSMI161610	16	406.4	16	406.4	10	254.0	12	304.8	18	457.2	12	304.8	12	304.8	14
BSMI161608	16	406.4	16	406.4	08	203.2	12	304.8	18	457.2	12	304.8	12	304.8	14
BSMI161606	16	406.4	16	406.4	06	152.4	12	304.8	18	457.2	12	304.8	12	304.8	14
BSMI161412	16	406.4	14	355.6	12	304.8	12	304.8	16	406.4	12	304.8	10	254.0	14
BSMI161410	16	406.4	14	355.6	10	254.0	12	304.8	16	406.4	12	304.8	10	254.0	14
BSMI161408	16	406.4	14	355.6	08	203.2	12	304.8	16	406.4	12	304.8	10	254.0	14
BSMI161406	16	406.4	14	355.6	06	152.4	12	304.8	16	406.4	12	304.8	10	254.0	14
BSMI161210	16	406.4	12	304.8	10	254.0	12	304.8	14	355.6	12	304.8	08	203.2	14
BSMI161208	16	406.4	12	304.8	08	203.2	12	304.8	14	355.6	12	304.8	08	203.2	14
BSMI161206	16	406.4	12	304.8	06	152.4	12	304.8	14	355.6	12	304.8	08	203.2	14
BSMI141412	14	355.6	14	355.6	12	304.8	10	254.0	16	406.4	10	254.0	10	254.0	14
BSMI141410	14	355.6	14	355.6	10	254.0	10	254.0	16	406.4	10	254.0	10	254.0	14
BSMI141408	14	355.6	14	355.6	08	203.2	10	254.0	16	406.4	10	254.0	10	254.0	14
BSMI141406	14	355.6	14	355.6	06	152.4	10	254.0	16	406.4	10	254.0	10	254.0	14
BSMI141210	14	355.6	12	304.8	10	254.0	10	254.0	14	355.6	10	254.0	08	203.2	14
BSMI141208	14	355.6	12	304.8	08	203.2	10	254.0	14	355.6	10	254.0	08	203.2	14
BSMI141206	14	355.6	12	304.8	06	152.4	10	254.0	14	355.6	10	254.0	08	203.2	14
BSMI121210	12	304.8	12	304.8	10	254.0	08	203.2	14	355.6	08	203.2	08	203.2	14
BSMI121208	12	304.8	12	304.8	08	203.2	08	203.2	14	355.6	08	203.2	08	203.2	14
BSMI121206	12	304.8	12	304.8	06	152.4	08	203.2	14	355.6	08	203.2	08	203.2	14
BSMI121008	12	304.8	10	254.0	08	203.2	08	203.2	12	304.8	08	203.2	06	152.4	14